

T-PROTECTIVE

TECHNICAL DATA SHEET

Product description

In addition to impregnating the wood, it makes it difficult the penetration of dirt. T-Protective restores the oil balance, specific to this type of material. It also brings out the colour of teak and it softens the surface to the touch.

Product information

Product code	W6915		
Colour	Neutral .000		
Specific gravity	UNI EN ISO 2811-1	0,80 ÷ 0,85 g/cm ³	
Flash point	UNI EN ISO 13736	60 °C	
Packaging	1 – 2,5 Lt		

Application and use

APPLICATION PROCEDURE

After cleaning the surface with T-Detergent and T-Bleaching, and when it is perfectly dry, apply T-Protective with a soft brush following the wood grains.

If you notice that wood rapidly absorbs this product, a second coat will be necessary. In this case, you will have to wait at least 30 minutes between the first and the second coat. With an external temperature of 20° C, this product needs about 12 hours to dry.

Storage

It is recommended to avoid exposure to air and extreme temperatures. To maximise the shelf life in the can, it is worth checking that the container is well closed during the storage and that temperature is between 10° C and 35° C. Avoid exposure to direct sunlight.

T-PROTECTIVE

TECHNICAL DATA SHEET

Safety rules

Comply with the provisions set by the local health and safety at work regulations. Avoid the contact with the skin for example. Operate in well ventilated places and, if in closed areas, use vacuum cleaners, fans and air conveyors. During the application, use appropriate protections (masks, gloves, glasses, etc). Before using, read section 7-8 of the SDS.

INSTRUCTIONS FOR THE DISPOSAL OF PRODUCTS AND PACKAGING

Empty packaging that contained products: Dispose of empty packaging according to the requirements of the waste disposal law, for example by taking them to the recycling centre.
Packages containing the unused products: Disposal of the unused product in accordance with the law of disposal of such waste, for example by taking it to a recycling centre; recycling of packaging is prohibited in this case. Do not empty into drains or water courses. Product packaging must be kept indoor and temperature in the storage place must be between 10° C and 35 °C. Do not expose to sunlight.

Notes

The values indicated in the present technical sheet can have slight variations from one batch to another.

The applied product must not come in contact with water, chemicals or be subjected to mechanical stress before curing is complete. The wet film thicknesses refer to the non-diluted product. With dilution, this value will rise. The above information is the result of accurate laboratory tests and practical experiences; however, since the product is predominantly used outside the manufacturer's control, Boero Bartolomeo S.p.A. can only guarantee its quality. The information contained in this sheet may be subject to revision by the Company. For clarification, updates or for further information, it is recommended to contact Boero Bartolomeo S.p.A directly. The present datasheet annuls and replaces every other to this one.